

DESKTOP BARCODE



LABEL PRINTER

LK-B10

- Thermal transfer and direct thermal printing
- Stable & reliable label printing
- High capacity memory
- Large capacity of roll (200mm OD) with external media holder
- Less ribbon replacement with 360M length (Wax, Resin, Wax/Resin)
- Paper width adjustable from 18mm to 118mm
- Selectable optional Auto cutter or Peeler
- Built-in internal power





● SPECIFICATION

ITEM	TYPE	
MODEL	LK-B10(LK-B11)	
PRINT METHOD	Thermal Transfer and Direct Thermal	
PRINTING SPEED	102 mm/sec	
PRINT WIDTH	104mm(4.1")	
PRINT LENGTH	630mm(24.8")	
RESOLUTION	203 DPI(8 dots/mm)	
PAPER WIDTH (min~max)	18mm ~ 118mm(0.7" ~ 4.25")	
PAPER ROLL SIZE (min~max)	Internal	Ø 25.4(1")~ Ø 127mm(5.0")
	External	Ø 38.1(1.5")~ Ø 200mm(7.8")
PAPER THICKNESS	0.06 ~ 0.20mm	
PAPER TYPE	Label, Tag, Continuous, Fanfold	
PAPER SENSOR	Label Gap Sensor, Black Mark Sensor, Notch Sensor	
RIBBON WIDTH	33mm ~ 110mm(1.3 ~ 4.3")	
RIBBON LENGTH	360M, Ø 67mm(2.5")	
MEMORY	STANDTAD	8MB SDRAM, 3.5MB Flash
	OPTION	16MB Flash
BARCODE	1D	Code39, Code128 with subsets A/B/C, Code 93, Codabar, Interleaved 2 of 5, UPC-A and UPC-E With 2 or 5 digit extensions, Postnet, Plessey, German Post Code, MSI-3
	2D	MaxiCode, PDF417, Datamatrix, QR Code, Code 49
FONT SPECIFICATION	6 bitmapped - 8x12, 10x16, 12x20, 14x24, 32x48, 24x24(KSC5601)	
PROGRAMMING LANGUAGE	EPLII Command compatible	
POWER	AC 100~240V, 24VDC, 2.5A	
DIMENSIONS	215mm x 287mm x 231mm	
WEIGHT(kg)	2kg	

INTERFACE




◀ **LK-B10 INTERFACE**
 Standard interface card
 - Serial(RS-232C)
 - Parallel(IEEE-1284)
 Optional interface card
 - USB

PEELER



AUTO CUTTER



<https://TactaTech.com> | تکتا

SEWOO TECH Co., Ltd.

374-2, Gajang-dong, Osan-si, Gyeonggi-do, 447-210, Korea

T. +82-31-459-8200 F. +82-31-459-8880

<http://www.miniprinter.com>

