

DESKTOP BARCODE



LABEL PRINTER

LK-B230

- Thermal transfer and direct thermal printing
- High Resolution : 300DPI (12 dots/mm)
- Stable & reliable label printing
- High speed 102mm per second
- High capacity memory
- Large capacity of roll (200mm OD) with external media holder
- Less ribbon replacement with 360M length (Wax, Resin, Wax/Resin)
- Paper width adjustable from 18mm to 118mm
- Selectable optional Auto cutter or Peeler





● SPECIFICATION

ITEM	TYPE	
MODEL	LK-B230	
PRINT METHOD	Thermal Transfer and Direct Thermal	
PRINTING SPEED	102 mm/sec	
PRINT WIDTH	104mm(4.1")	
PRINT LENGTH	650mm(25.5")	
RESOLUTION	300 DPI(12 dots/mm)	
PAPER WIDTH (min~max)	18mm ~ 118mm(0.7" ~ 4.64")	
PAPER ROLL SIZE (min~max)	Internal	Ø 25.4(1")~ Ø 127mm(5.0")
	External	Ø 38.1(1.5")~ Ø 200mm(7.8")
PAPER THICKNESS	0.06 ~ 0.20mm	
PAPER TYPE	Label, Tag, Continuous, Fanfold	
PAPER SENSOR	Label Gap Sensor, Black Mark Sensor, Notch Sensor	
RIBBON WIDTH	33mm ~ 110mm(1.3 ~ 4.3")	
RIBBON LENGTH	360M, Ø 67mm(2.63")	
MEMORY	STANDTAD	8MB SDRAM, 5MB Flash
	OPTION	16MB Flash
BARCODE	1D	Code39, Code128 with subsets A/B/C, UCC/EAN-128, Code 93, Codabar, Interleaved 2 of 5, UPC-A, UPC-E, UPC-A and UPC-E with 2 or 5 digit extensions, Postnet, Plessey, German Post Code, MSI-3
	2D	MaxiCode, PDF417, Datamatrix, QR Code, Code 49
FONT SPECIFICATION	7 bitmapped-5x9, 7x11, 10x18, 15x28, 13x26, 40x60, 13x21	
	1 Smooth Scalable	
PROGRAMMING LANGUAGE	ZPLII Command compatible	
POWER	AC100~240V, 24VDC, 2.92A	
DIMENSIONS	215mm x 287mm x 231mm	
WEIGHT(kg)	3.6kg	

INTERFACE



◀ LK-B230 INTERFACE


Standard interface card
- USB
- Parallel(IEEE-1284)

Optional interface card
- Serial(RS-232C), Ethernet,
Wi-Fi 802.11b/g

PEELER



AUTO CUTTER



<https://TactaTech.com> | تکتا

SEWOO TECH Co., Ltd.

374-2, Gajang-dong, Osan-si, Gyeonggi-do, 447-210, Korea

T. +82-31-459-8200 F. +82-31-459-8880

<http://www.miniprinter.com>

